



# HIFULL HB-612

## HYDROPHOBIC FUMED SILICA

HB-612 is hydrophobic fumed silica which produced by hydrophilic fumed silica with specific surface area of 150m<sup>2</sup>/g after chemical post-treatment with HMDS (Hexamethyldisilazane).

## 01 Applications

- RTV silicone rubber
- Adhesives and Sealants
- Coatings & Printing ink
- Powder Coatings

## 02 Properties

- Rheological control of RTV silicone rubber
- Anti-settling, anti-sagging and thixotropy agent
- Free flow aid and anti-caking aid for powders
- Thixotropic agent & reinforce filler for RTV silicone sealants, the hydrophobic feature enables RTV silicone sealants a long guarantee time

## 03 Physical & Chemical Data

Properties	Unit	Typical Value	Testing Standard
Specific Surface Area (BET)	m <sup>2</sup> /g	140±20	GB/T 20020
Carbon Content ( Based on material dried at 105°C for 2 hours)	%	0.7~1.3	GB/T 20020
PH (4% suspension) (water : ethanol is 1:1)	—	5.0~8.0	GB/T 20020
Loss on drying( 2 hours at 105°C)	%	≤0.7	GB/T 20020
Loss on ignition (2 hours at 1000°C, based on material dried for 2 hours at 105°C)	%	≤2.0	GB/T 20020
Tamped Density (Based on material dried at 105°C for 2 hours)	g/L	40~60	GB/T 20020
Silica Content (Based on ignited material)	%	≥99.8	GB/T 20020

※ customized products available for special physical or chemical data